



- FEATURES:**
- Non Perishing to rubber
 - Stops galling & binding
 - Di-electric properties to 70kV
 - Food Grade
 - Long-term Biodegradable
 - Non Toxic
 - Non Carcinogenic
 - Non Leaching
 - Acid & Salt Resistant

- PACK SIZES:**
- | | |
|-----------------|-----------|
| • 250ml Tube | [GS\250T] |
| • 235ml Tub | [GS\0235] |
| • 500ml Tub | [GS\0500] |
| • 1 Litre Pail | [GS\0001] |
| • 4 Litre Pail | [GS\0004] |
| • 20 Litre Pail | [GS\0020] |

CONTENTS: Pure industrial grade lanolin

USES:

- Anti-seize for threaded rod, nuts & bolts
- Assembly lubricant
- Corrosion & moisture proofing for multi-pin connectors
- Prevents galling of stainless steel and aluminium
- Wire rope lubrication and corrosion protection
- Lubricant for rubber hoses, linkages, pivot pins & bushes
- Stops electrolysis due to similar metals
- Belt dressing

PHYSICAL PROPERTIES:

- Appearance: Light brown coloured solid
- Boiling Point: Approx. >250°C
- Flash Point: >200°C
- Specific Gravity: 0.90 @ 20°C
- Solubility in Water: Insoluble

STORAGE & TRANSPORT:

- Lanotec Type A Grease is not classified as Dangerous Goods
- No specific storage required

For safe handling of this product, please consult the product material safety data sheet (MSDS)



NATURALLY BETTER

www.lanotec.com.au | www.youtube.com/LanotecAus

Contact Details for further information:

Ph: +61 7 3373 3700 | Fax: +61 7 3373 3777 | E: info@lanotec.com.au

Always read entire label before using product

APPLICATION:

- Smear onto thread and underside of bolt head. Wipe off excess before tensioning.
- Fill one half of electrical plug to create moisture / dust proof barrier before reconnecting electrical connector.
- Smear grease between dissimilar metals before tightening.
- Smear one flange face only for use as a soft seal gasket.
- Smear O-ring or seal with Type A Grease to hold in place during assembly.
- For wire rope: wipe onto wire rope by hand whilst undertaking regular inspection, or use pressurised applicator such as Masto, Viper, or Raptor.
- Apply directly to squealing belt as a belt dressing (softens and moisturises belt).
- Apply via pump or hand to all shafts and pins prone to drying out or seizing.

REMOVAL:

- If removal of Lanotec Type A Grease is required, Lanotec Citra-Force or Lanotec PowaWash is recommended

APPROVALS:

- HACCP Australia Food Safety Accreditation Systems - Food Grade Lubricant
- AQIS Acceptance of Chemical Compound for use in Export Meat Establishments - Category 10 Lubricant Type A
- NZFSA Approval Lubricant C12
- Halal Certification Authority Australia - Taher Accreditation

For safe handling of this product, please consult the product material safety data sheet (MSDS)



NATURALLY BETTER

www.lanotec.com.au | www.youtube.com/LanotecAus

Contact Details for further information:

Ph: +61 7 3373 3700 | Fax: +61 7 3373 3777 | E: info@lanotec.com.au