



## BIANCO VULCAN 6.5HP PORTABLE PETROL ENGINE TWIN STAGE FIRE PUMP

The pump is a compact self priming engine driven pump supplied ready to operate with hose fittings and suction strainer.

### The pump is characterised by:

- Single cylinder, 4 stroke, forced air cooled, Briggs & Stratton OHV Engine
- Heads to 80 metres
- Flows to 300 l/min
- Suction to 6m/120s
- 1 x 1.5" 2 x 1" BSP male discharge ports
- 1 x 1.5" BSP male suction port
- Rubber mounting feet
- Low oil level engine protection

### Features:

- Next generation engine and pump design
- 800 hour high performance engine
- Dura-bore™ cast iron cylinder liners for longer life
- Lo-Tone™ muffler for reduced noise
- Low emissions to recognised global standards
- Full national engine support across 400+ Briggs & Stratton service centres
- Spark arrester with deflector
- Low oil sensor
- Full serviceability without removing pump from frame
- Heavy duty fuel cap
- Multi-Point discharge port
- Custom built frame

### Applications:

- Fire Fighting
- Water Transfer
- Tank Filling
- Crop Spraying and Irrigation

Liquid:	Engine Data:
<b>Liquid Type:</b> Clean Water Clean water temperature range: 2 - 35° C	<b>Type:</b> Single Cylinder, Aircooled, 4 Stroke OHV, Briggs & Stratton I/C Series
<b>Materials:</b>	<b>Model:</b> 130G320117H1
<b>Pump Body:</b> Aluminium	<b>HP gross:</b> 6.5
<b>Impeller:</b> Aluminium	<b>Displacement:</b> 208 cc
<b>Mechanical Seal:</b> Carbon/Ceramic/Nitrile	<b>Air Cleaner:</b> Dual Element, Paper and Foam
<b>O rings:</b> Nitrile	<b>Ignition:</b> CDI
<b>Installation:</b>	<b>Starting:</b> Recoil
<b>Maximum ambient temperature:</b> 40°C	<b>Fuel Capacity:</b> 3.1 Litre
<b>Self Priming Time at 5m:</b> <120 seconds	<b>Oil Capacity:</b> 0.6 Litre
<b>Weight:</b>	
29.2kg	

